

[24] Fig. 11 illustrates the slot location within the waveguide. The cross-machine coordinate is z and $h(z)$ is the local elevation of the slot above the bottom of the waveguide. The overall active cross-machine length is L .

REMARKS


The present Amendment merely moves certain language from Fig. 11 to the specification to comply with all formal drawing requirements.

If there is any fee due in connection with the filing of this Preliminary Amendment, please charge the fee to our Deposit Account No. 06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

Dated: January 11, 2002

By: 
Lori-Ann Johnson
Reg. No. 34,498

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

NE 1000 1

Application Number: 09/941,044
Filing Date: August 28, 2001
Attorney Docket Number: 7648.0022

APPENDIX TO PRELIMINARY AMENDMENT OF JANUARY 11, 2002
VERSION WITH MARKINGS TO SHOW CHANGES MADE

AMENDMENTS TO THE SPECIFICATION

[24] Fig. 11 illustrates the slot location within the waveguide. The cross-machine coordinate is z and $h(z)$ is the local elevation of the slot above the bottom of the waveguide. The overall active cross-machine length is L .

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com